

Description and field of use:

MILPOL is used for painting interior walls and ceilings. It contains no preservatives or solvents and softening and is psychologically acceptable. It is especially acceptable internal color for allergic persons. MILCOLOR is used for painting external walls (facade surfaces) with previously applied mineral surfaces.

Composition:

Based on vinyl acetate copolymer (Milpol)

Based on the dispersion of connective means (Milcolor)

Properties:

MILPOL:

- Highly expressed cover
- high water vapor
- Good connective for mineral surfaces
- Luster dull matt
- Washable

MILCOLOR:

- Highly expressed cover
- high hydrophobicity
- Resistance to external influences
- Effect of fungicidal and algicidal effect

Surface preparation:

The surface should be dry, clean, without loose parts and cracks. Before painting surface should be impregnated with MILFAS GRUND.

Material preparation and processing:

It is applied by roller or brush. If the surface has a pronounced absorption feature dilute the first the maximum 10% of water with stirring. Another coat of paint can be applied after 12 hours. The second coat is diluted with up to 3% water. Color is completely dry after 24 hours, depending on the weather conditions. Wash tools immediately after use. Do not mix with other coatings or solvents.

Processing conditions:

ubstrate and air temperature should be from +5 to 30 ° C. Areas under direct action of sun and strong wind should be protected by protective curtain. Drying period (at T = 20 ° C, relative humidity 65%) approximately 4-6 hours (touch dry), or approximately 24 h (state when protection from precipitation is not needed).

Consumption:

0,15-0,25 kg/m²

Packaging:

PVC bucket 25kg.

Milpol i:

PVC bucket 10 and 5kg

Storage:

At least 18 months (Grund-A i Grund-S), 12 months (Milfas 12) in original unopened container in a dry and ventilated areas, protected from direct effects of the sun. MUST NOT FREEZE!

Safety warning:

Irritant. Protect skin, mucous membrane and eyes.



mili evi d.o.o. Kreševo, BiH

Technical instructions provided in this publication are based on our experience and are provided in order to achieve the optimal results in using this product. For damages caused by wrong choice of product, its irregular application or low quality work we do not accept responsibility. This data sheet complements and replaces all previous editions. Milicevic Ltd. Kresevo reserves the right to all subsequent changes and additions.